OUPONTE

Flashing Products

The right protection for every type of window and door.

***OUPONT**

Flashing Tape

Cost-effective way to protect the jambs and heads of **residential** and **multifamily** windows from water intrusion.





4" x 75' | 6" x 75' | 9" x 75' | 12" x 75'



COUPONT

FlexWrap.

Seamless protection of 3-D window sills, custom windows, and half round arched windows for **residential** and **commercial** construction.



6" x 75' (for 2x4 framing) | 9" x 75' (for 2x6 framing)



COUPONT

StraightFlash.

A premium, durable, 100% butyl-backed, self-adhered flashing material for **straight** jambs and heads of rectangular windows and doors to help prevent winddriven rain and stop air penetration.

ROLL SIZES: 4" x 150' | 9" x 125'



COUPONT

VersaFlange

Unique **dual-sided**, self-adhered flashing tape used for brick mould and non-flanged windows and doors for residential and commercial construction.



ROLL SIZE:

© Copyright 2024 WPL. All rights reserved. DuPont™, DuPont™ FlexWrap™, DuPont™ StraightFlash™, DuPont™ Tyvek®, and DuPont™ Flashing Systems are registered trademarks or trademarks of DuPont or its affiliates

∢DHPC

FlexWrap EZ

An easy-to-apply, self-adhered, flexible flashing for sealing smaller exterior electrical, heating, ventilation and air conditioning



(HVAC) and plumbing penetrations.

ROLL SIZE: 2 3/4" x 15'

FlexWrap EZ

OUPONT

Tyvek.

IntegrationWrap[®]

ROLL SIZE:

A simple and effective method for integrating DuPont self-adhered window flashings with Tyvek® for window first installations.



Tower® AU-1 Sealant

Durable, highly-flexible sealant for window and door installation and general construction. Formulated to bond with DuPont™ Building Envelope Solutions and a wide range of building substrates.



DuPont™ Flashing Systems Benefits:

Easy installation

Quick release backing

Superior protection from water damage

Butyl adhesive performs through extreme temperature

Contains no asphalt

Designed for 120 days of UV exposure Forgiving initial tack, easily repositioned Durable, tough, tear-resistant

800.288.9835 <u>WeatherizationPar</u>tners.com WP L

Pushing the Envelope™